




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

|  |    |   |
|--|----|---|
| (51) International Patent Classification <sup>6</sup> :<br>B65D 41/04  | A1 | (11) International Publication Number: WO 96/26121<br>(43) International Publication Date: 29 August 1996 (29.08.96)  |
| (21) International Application Number: PCT/GB96/00346<br>(22) International Filing Date: 14 February 1996 (14.02.96)<br><br>(30) Priority Data:<br>9503430.2 21 February 1995 (21.02.95) GB<br>9516347.3 9 August 1995 (09.08.95) GB<br><br>(71) Applicant (for all designated States except US): MCG CLOSURES LIMITED [GB/GB]; P.O. Box 32, Bromford Lane, West Bromwich, West Midlands B70 7HY (GB).<br><br>(72) Inventor; and<br>(75) Inventor/Applicant (for US only): THOMPSON, Nigel [GB/GB]; 45 Lea Vale Road, Norton, Stourbridge, West Midlands DY8 8AT (GB).<br><br>(74) Agents: STEBBING, Peter, John, Hunter et al.; Ablett & Stebbing, 45 Lancaster Mews, Lancaster Gate, London W2 3QQ (GB). |    | (81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AZ, BY, KG, KZ, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).<br><br><b>Published</b><br><i>With international search report.<br/>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i> |

(54) Title: SELF-CENTERING CONTAINER CLOSURE

## (57) Abstract

The invention provides a container closure moulded in one piece from a plastics material and comprising a crown (11), a dependent skirt (12), the radially inner surface of which is formed with a screw thread (13), a surface (16) which is flared in a direction away from the top being formed on the internal surface of the skirt where it joins the crown and an annular resilient fin (18) extending downwardly and outwardly from an articulation position (26) on the underside of the top at position spaced radially inward of said flared surface having a length such as to permit at least its portion adjoining its free edge to lie against the flared surface (16), wherein the fin is deformed outwardly by the top of the neck of the container to which the closure is to be applied, characterised by a continuous or discontinuous locator annulus (30) depending downwardly from the undersurface of the crown (11) and disposed radially inwardly of the fin (18), the locator annulus extending downwardly by a distance greater than the fin (18) and having an outer diameter just smaller than that of the inner diameter of the container neck (20) with which it is to be used. Closures of this type allow effective reliable capping.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

|    |                          |    |  |    |                          |
|----|--------------------------|----|--|----|--------------------------|
| AM | Armenia                  | GB | United Kingdom                           | MW | Malawi                   |
| AT | Austria                  | GE | Georgia                                  | MX | Mexico                   |
| AU | Australia                | GN | Guinea                                   | NE | Niger                    |
| BB | Barbados                 | GR | Greece                                   | NL | Netherlands              |
| BE | Belgium                  | HU | Hungary                                  | NO | Norway                   |
| BF | Burkina Faso             | IE | Ireland                                  | NZ | New Zealand              |
| BG | Bulgaria                 | IT | Italy                                    | PL | Poland                   |
| BJ | Benin                    | JP | Japan                                    | PT | Portugal                 |
| BR | Brazil                   | KE | Kenya                                    | RO | Romania                  |
| BY | Belarus                  | KG | Kyrgyzstan                               | RU | Russian Federation       |
| CA | Canada                   | KP | Democratic People's Republic<br>of Korea | SD | Sudan                    |
| CF | Central African Republic | KR | Republic of Korea                        | SE | Sweden                   |
| CG | Congo                    | KZ | Kazakhstan                               | SG | Singapore                |
| CH | Switzerland              | LI | Liechtenstein                            | SI | Slovenia                 |
| CI | Côte d'Ivoire            | LK | Sri Lanka                                | SK | Slovakia                 |
| CM | Cameroon                 | LR | Liberia                                  | SN | Senegal                  |
| CN | China                    | LT | Lithuania                                | SZ | Swaziland                |
| CS | Czechoslovakia           | LU | Luxembourg                               | TD | Chad                     |
| CZ | Czech Republic           | LV | Larvia                                   | TG | Togo                     |
| DE | Germany                  | MC | Monaco                                   | TJ | Tajikistan               |
| DK | Denmark                  | MD | Republic of Moldova                      | TT | Trinidad and Tobago      |
| EE | Estonia                  | MG | Madagascar                               | UA | Ukraine                  |
| ES | Spain                    | ML | Mali                                     | UG | Uganda                   |
| FI | Finland                  | MN | Mongolia                                 | US | United States of America |
| FR | France                   | MR | Mauritania                               | UZ | Uzbekistan               |
| GA | Gabon                    |    |  | VN | Viet Nam                 |

- 1 -

SELF-CENTERING CONTAINER CLOSURE

The present invention relates to a self-centering container  
5 closure particularly of the type adapted for utilisation with  
a gaseous liquid.

Container closures moulded in one piece from a plastics  
material are well known in the art. One such is disclosed in  
10 our earlier European Patent No. 0136088 which relates to a  
container closure moulded in one piece from a plastics  
material and comprising a top (or crown), a dependent skirt  
the radially inner surface of which is formed with screw  
thread, a surface which is flared in a direction away from the  
15 top being formed on the internal surface of the skirt where  
it joins the top, and an annular resilient flexible fin  
extending downwardly and outwardly from the underside of the  
top at a position spaced regularly inwardly in said flared  
surface and having a length such as to permit at least its  
20 portion adjoining its free edge to lie against said flared  
surface when the fin is deformed outwardly by the rim of the  
neck of a container to which the closure is to be applied.

Whereas closures of this type work satisfactorily but there  
25 remains the problem of centralising the cap on the container  
in a really reliable way and of preventing "cocking" which is  
occasioned during capping. During capping it is difficult to  
ensure that the plane of the crown becomes perpendicular to  
the axis of the container neck prior to rotation. This is not  
30 always possible during high speed capping and accordingly a  
problem arises when the caps are screwed rapidly onto the  
container necks. Whereas a certain tolerance in the screw-  
thread portions can allow a degree of "cocking" to be  
corrected during capping, it is relatively easy to destroy the  
35 closures during the capping procedure due to this defect.

- 2 -

Container closures including downwardly depending internal bore seals are also known in the art. The purpose of these arrangements is to enable a cap to be rapidly screwed onto a container neck such that the rim of a container neck seals  
5 against the underside of the crown, whereas the internal bore of the container neck is in sealing contact with the bore seal annulus.

In a full bottle of a carbonated beverage as the temperature  
10 rises, gas tends to come out of solution and to increase the gas pressure in the container. This tends to force the underside of the crown of container closure upwardly thereby overcoming the lateral pressure exerted on the inner face of the prior art bore seals and thereby allows a fluid path to  
15 open up between the outer face of the bore seal and the inner face of the container neck towards the rim. Simultaneously a doming effect impairs the seal between the underside of the crown and the rim of the container neck. Accordingly gaseous escape paths are generated and gas escapes from the container.  
20 The consumer can therefore be left with a "flat" contents. This effect is accentuated if scratches are present on the rim of the container neck because these also tend to allow gas to escape. This is an especial problem with recycled containers.

25 The present invention has as its object the alleviation of these problems by providing closures of the foregoing general type provided with means for self-centering during capping and means for alleviating the problem of cocking.

30 In a further aspect of the present invention, the invention also provides means for reducing the incidence of doming. The arrangement of the invention can also reduce the possibility of successful tampering because the closure is retained substantially coaxial in the container neck.

35

The invention is characterised by a continuous or discontinuous locator annulus depending downwardly from the

- 3 -

under surface of the crown and disposed radially inwardly of the fin annulus, the locator annulus extending downwardly by a distance greater than that of the fin and having an outer diameter just smaller than the inner diameter of the container neck with which it is to be used. The distance may be up to 100% longer than the corresponding distance from the underside of the crown to the fin.

The fin may be bulbous at its remote end and may be provided with a neck contact surface inclined inwardly and upwardly towards the crown for contact in use with the outer rim of the container neck. Preferably the central point of an articulation portion of the fin is located along a line parallel to the axis of the closure and within the outer one half of the diameter of the container neck with which the closure is to be used. In a preferred embodiment, the central point of the articulation portion is within the outer one third or even one quarter of the diameter of the container neck.

The articulation portion may have a radial thickness greater than one quarter of the radial thickness of the bulbous fin. This means that when the closure has been centered on the neck by operation of the locator annulus, the inclined surface of the bulbous fin contacts the outer rim of the container neck and, since the closure is rotating and since the bulbous fin is a relatively strong annulus, the inclined surface thereof tends to further ensure centering of the closure prior to and during deformation. By this means, "cocking" is alleviated since contact under rotation tends to locate the closure in its correct orientation perpendicular to the axis of the closure.

The angle of the inclined plane of the bulbous fin is preferably between about 35° and 55° and most preferably about 45° relative to the axis of the container closure.



- 4 -

The remote end of the locator annulus may be chamfered or the radially outer remote end thereof may be inwardly and downwardly inclined so as to present an outwardly and upwardly inclined surface to the inner rim of the container neck.

5 Preferably the upper end of the inclined plane of the locator annulus terminates at or adjacent a notional plane horizontal to the axis of the closure which is also generally coincident with the lower end of the inclined contact surface of the bulbous fin. Thus, the two mutually opposed inclined planes

10 respectively of the bulbous fin and the locator annulus operate sequentially upon a container rim. The angle of the inclined plane of the locator annulus is preferably 25° to 35° relative to the axis of the container closure.

15 It will also be appreciated that the positioning of the locator annulus radially inwardly of the fin has the effect of strengthening the crown against "doming". Thus a combination of the fin (preferably bulbous) and the locator annulus is particularly effective in resisting doming and its

20 effects on the seal achievable by the fin outboard thereof. The closures of this type are most preferably made by injection moulding.

The invention will now be described, by way of illustration

25 only with reference to the accompanying drawings which show in Figures 1 and 2 fragmentary elevations illustrating the closures in accordance with the present invention prior to, and on application.

30 The closure 10 is moulded in one piece from a resilient plastics material and has a top (crown) 11 and a dependent skirt 12 formed with an internal screw thread 13 and external knurling 14. A corner region 15 at the upper end of the skirt is thickened and has a conically flared internal surface 16

35 extending at an angle of about 30° from the axis of the closure 10. Spaced radially inwardly of the surface 16 is a resilient bulbous fin 18 which extends from an articulation

- 5 -

point 26 on the under side of the top 11. The bulbous fin 18 thus depends downwardly from the articulation point 26. The radially inner surface 27 extends generally parallel to the plane of the skirt 12 whereas the radially outer portion 28  
5 of the bulbous fin is curved generally radially outwardly and downwardly to define at its remote end an outer sealing portion 19. The outer sealing portion is conjoined to the inner radially inner surface 27 by means of an inclined plane 25 having an angle of about 45°.

10

Closures of this type may be produced, preferably by injection moulding, with or without a tamper evident band. Preferably the skirt terminates in a plurality of frangible bridges 34 supporting a tamper evident band 35 for cooperation with a  
15 plain security band 36 on the outer neck portion of a container neck 20 in the usual way.

In use, the container closure 10 is applied to a neck 20 of a container so that the rim 21 of the container neck moves  
20 upwardly as in Figure 1 to adopt the position shown in Figure 2. As it does so, the inclined plane 25 of the bulbous fin 18 comes into contact with the outer rim portion 22 of the container neck 20 while the closure 10 is being rotated during the capping operation. This has the subsequent effect of  
25 assisting in a centering action such that the axis of the container closure and the container neck become coaxial with more certainty. Further rotation of the container closure 10 relative to the container neck 20 causes the container neck to move upwardly relative to the container closure to adopt  
30 the position shown in Figure 2. It will be noted in that the articulation of point 26 is disposed approximately one third of the radial distance between the inner and outer surface of the container neck such that the bulbous fin 18 is deformed radially outwardly to seal between the inclined surface 25 and  
35 conically flared internal surface 16. At the same time, because of this radial displacement, there is a pivotal force applied to the internal surface of the crown closure which

- 6 -

tends to resist doming in conjunction with the locator annulus 30 referred to below.

Arrangements of the foregoing type are used with the main  
5 feature of the invention shown in Figures 1 and 2, i.e. the  
locator annulus 30. Disposed radially inwardly of the bulbous  
fin 18, the locator annulus 30 has a external diameter 32  
which is just smaller than the inner diameter of the internal  
surface 29 of the container neck. The locator annulus 30 is  
10 provided therefore with a radially inner face 31, a radially  
outer face 32, said radially outer face 32 culminating towards  
its remote end in an annular inclined plane 33 which extends  
upwardly and outwardly towards the inner face of the container  
neck 29.

15

In use during the capping procedure, the inner rim portion 23  
which is radiused comes into contact with the inclined plane  
of the locator annulus 33 which has the effect of centering  
the container closure on the container neck. As the cap is  
20 rotated, there is relative movement between the container neck  
20 and the closure 10 such that it adopts the position shown  
in Figure 2. Because the locator annulus is not intended as  
a seal but essentially and primarily as a locator means, the  
sealing effect is to be found between the outer rim portion  
25 22 and the bulbous fin 18. The effect of this is that because  
the closure 10 is correctly orientated relative to the  
container neck 20 the problems of "cocking" and centering are  
correctly addressed.

30 Further and probably as importantly, because the locator  
annulus is disposed in-board of the bulbous fin, it tends to  
strengthen the central portions of the crown 11. This resists  
doming.

35 The locator annulus 30 has the further effect of retaining the  
closure coaxially upon the container neck thus resisting  
tampering.



- 7 -

It will thus be seen that during application of the closure 10 to the container neck 20, the rim of the container 21 first comes into contact with the inclined surface 33 of the locator annulus 30 prior to any contact of the bulbous fin 18. This tends to center and directly orientate the closure relative to the container neck. Subsequently the outer rim portion 22 of the container neck 20 comes into contact with the inclined plane 25 which has a further centering and anti-cocking action as a primary factor with the secondary effect of causing the bulbous fin 18 to articulate at the point 26 as such that the surface 28 comes into contact with the conically flared internal surface 16 thereby causing effective sealing.

It will also be appreciated that by virtue of the relative thickness of the bulbous fin 18 taken with the effects of the locator annulus, a more effective seal is provided than previously. The locator annulus also tends to absorb all lateral forces of application generated by the combination of the application of force and the helical angle of the container/closure threads. This ensures that none of these forces impinge upon the bulbous fin 18 such that the same is inconsistently engaged with the container.

The locator annulus and the stiffness of the closure crown together have the effect that any doming of the crown under pressure will only take place within the circumference of the locator annulus 30. This has two effects. In the first place it reduces the effects of doming upon the bulbous fin 18 thus ensuring that the fin does not get pulled out of sealing engagement with the container during cases of extreme doming. Further the locator ring acts as a stiffening rib which resists and reduces the degree of doming exerted by the internal force. This tends to reduce storage problems when the containers are stacked.

This invention is particularly desirable when applying a closure to returnable containers where there is a risk of

- 8 -

possible damage to the outside corner/surface of the container which might provide a leakage path past the bulbous fin seal in high temperature storage conditions where doming can be expected.

5

The inventive closures are preferably made by injection moulding of high density polyethylene plastics materials. The locator annulus is intended to have no sealing properties and hence needs to be used in conjunction with a primary seal for  
10 example as hereinbefore set forth.

The invention provides therefore a closure as hereinbefore set forth and an assembly thereof with container closure.

- 9 -

## CLAIMS:

1. A container closure moulded in one piece from a plastics material and comprising a crown 11, a dependent skirt 12, the  
5 radially inner surface of which is formed with a screw thread 13, a surface 16 which is flared in a direction away from the top being formed on the internal surface of the skirt where it joins the crown and an annular resilient fin 18 extending downwardly and outwardly from an articulation position 26 on  
10 the underside of the top at position spaced radially inward of said flared surface having a length such as to permit at least its portion adjoining its free edge to lie against the flared surface 16, wherein the fin is deformed outwardly by the top of the neck of the container to which the closure is  
15 to be applied,  
characterised by a continuous or discontinuous locator annulus 30 depending downwardly from the undersurface of the crown 11 and disposed radially inwardly of the fin 18, the locator annulus extending downwardly by a distance greater than the  
20 fin 18 and having an outer diameter just smaller than that of the inner diameter of the container neck 20 with which it is to be used.
2. A container closure as claimed in claim 1 characterised  
25 in that the fin 18 is bulbous at its remote end and is provided with a rim contact surface 25 inclined inwardly and upwardly toward the crown for contact in use with the outer rim 22 of the container neck 20, and wherein the fin is bulbous and the central point of articulation 26 of the  
30 bulbous fin 18 is located along a line parallel to the axis to the closure and within the outer one half of the diameter of the container neck 20 with which it is to be used.
3. A container according to either preceding claim wherein  
35 the central point of articulation 26 is located within the outer one third of the container neck diameter.

- 10 -

4. A closure according to any preceding claim wherein the articulation portion has a radial thickness greater than one quarter of the radially thickness of the bulbous portion of a fin 18.

5

5. A closure according to any preceding claim wherein the inclined surface of the bulbous fin at an angle to the axis of the closure of 35° to 55°.

10 6. A closure according to any of claims 1 to 5 wherein the distance between the underside of the crown and the remote end of the locator annulus 30 is up to 100% longer than the distance between the underside of the crown and the remote tip 19 of the fin 18.

15

7. A closure according to any of claims 1 to 6 wherein the remote end of the locator annulus 30 terminates in an outwardly and upwardly inclined portion 33 to present an outwardly and upwardly inclined surface to the inner rim 23  
20 of the container neck 20 during capping.

8. A closure according to claim 7 wherein the upper end of the inclined portion of the locator annulus terminates at or adjacent a notional plane horizontal to the axis of the  
25 closure which plane is below or coincident with, the free end 19 of the bulbous fin 18.

9. A closure according to claim 8 wherein the mutually opposed inclined planes respectively of the locator annulus  
30 33 and the bulbous fin 25 are adapted to operate sequentially on opposite sides of the rim 21 during capping.

10. A closure according to any of claims 1 to 9 wherein the angle of the inclined plane 33 of the locator annulus 30 is  
35 25° to 35° relative to the axis of the closure.

- 11 -

11. A closure according to any preceding claim wherein the skirt portion terminates in a plurality of frangible bridges supporting a tamper evident band for cooperation with a plain security band on the outer neck portion of the container.


5

12. A closure according to any preceding claim made by injection or compression moulding.

13. An assembly of a container having a screw threaded neck  
10 and a closure according to any one of the preceding claims.




FIG. 1



2/2

FIG. 2



# INTERNATIONAL SEARCH REPORT

Inter national Application No  
PCT/GB 96/00346

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 6 B65D41/04

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 6 B65D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

| Category * | Citation of document, with indication, where appropriate, of the relevant passages           | Relevant to claim No. |
|------------|--|-----------------------|
| A          | FR,A,2 327 930 (ALCA S.A.) 13 May 1977<br>see claims; figure<br>---                          | 1,6,<br>11-13         |
| A          | EP,A,0 575 987 (MOULDTEC PVG AG) 29<br>December 1993<br>see abstract; figure 1<br>---        | 1,11-13               |
| A          | GB,A,2 046 720 (WALTER WIEDMER AG) 19<br>November 1980<br>see abstract; figures<br>---       | 1,3,6,7,<br>10,13     |
| A          | US,A,3 067 900 (KESSLER) 11 December 1962<br>see column 2, line 18 - line 45; figures<br>--- | 2                     |
| A          | EP,A,0 293 901 (METAL CLOSURES LTD.) 7<br>December 1988<br>---                               |                       |
|            | -/--   |                       |

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents :

- \* "A" document defining the general state of the art which is not considered to be of particular relevance
- \* "E" earlier document but published on or after the international filing date
- \* "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \* "O" document referring to an oral disclosure, use, exhibition or other means
- \* "P" document published prior to the international filing date but later than the priority date claimed

- \* "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \* "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \* "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \* "&" document member of the same patent family

Date of the actual completion of the international search

13 June 1996

Date of mailing of the international search report

28.06.96

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax (+31-70) 340-3016

Authorized officer

SERRANO GALARRAGA, J

# INTERNATIONAL SEARCH REPORT

Int. Patent Application No  
PCT/GB 96/00346

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

| Category * | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
|------------|--|-----------------------|
| A          | EP,A,0 316 167 (DAINIPPON INK AND<br>CHEMICALS INC) 17 May 1989<br>---             |                       |
| A          | DE,U,93 14 226 (OBERLAND GLAS AG) 26<br>January 1995<br>---                        |                       |
| A          | DE,A,41 35 109 (HEINRICH STOLZ GMBH) 29<br>April 1993<br>-----                     |                       |

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 96/00346

| Patent document<br>cited in search report | Publication<br>date | Patent family<br>member(s) | Publication<br>date |
|---|---------------------|----------------------------|---------------------|
| FR-A-2327930                              | 13-05-77            | NONE                       |                     |
| -----                                     | -----               | -----                      | -----               |
| EP-A-575987                               | 29-12-93            | DE-A- 4221004              | 05-01-94            |
| -----                                     | -----               | -----                      | -----               |
| GB-A-2046720                              | 19-11-80            | CH-A- 635795               | 29-04-83            |
|   |                     | AT-B- 385013               | 10-02-88            |
|   |                     | BE-A- 882587               | 31-07-80            |
|   |                     | DE-A- 3008838              | 16-10-80            |
|   |                     | FR-A,B 2453086             | 31-10-80            |
|   |                     | LU-A- 82315                | 02-07-80            |
|   |                     | NL-A- 8001835              | 07-10-80            |
| -----                                     | -----               | -----                      | -----               |
| US-A-3067900                              | 11-12-62            | NONE                       |                     |
| -----                                     | -----               | -----                      | -----               |
| EP-A-293901                               | 07-12-88            | AU-B- 570997               | 31-03-88            |
|   |                     | AU-B- 3227584              | 28-02-85            |
|   |                     | CA-A- 1282033              | 26-03-91            |
|   |                     | EP-A,B 0136088             | 03-04-85            |
|   |                     | JP-A- 60068256             | 18-04-85            |
|   |                     | US-A- 4526284              | 02-07-85            |
| -----                                     | -----               | -----                      | -----               |
| EP-A-316167                               | 17-05-89            | JP-A- 1139348              | 31-05-89            |
|   |                     | US-A- 4907709              | 13-03-90            |
| -----                                     | -----               | -----                      | -----               |
| DE-U-9314226                              | 26-01-95            | NONE                       |                     |
| -----                                     | -----               | -----                      | -----               |
| DE-A-4135109                              | 29-04-93            | NONE                       |                     |
| -----                                     | -----               | -----                      | -----               |